


CERTIFICATE OF FACSIMILE TRANSMISSION

I hereby certify that the following papers are being transmitted by facsimile to the International Bureau of WIPO at 41-22-740-1435 on the date shown below:

Amendment Under Article 19
Replacement Pages 11-14

YOU SHOULD RECEIVE A TOTAL OF 5 PAGES. Kindly confirm receipt of this transmission.

June 14, 2004
Date


Dana A. Lozon

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Johnson Controls Technology Company
International Appln. No. : PCT/US2003/037196
International Filing Date : November 19, 2003
For : COVERED ILLUMINATED VANITY MIRROR ASSEMBLY

International Bureau of WIPO
34 chemin des Colombettes
1211 Geneva 20
Switzerland

Dear Sir:

AMENDMENT UNDER ARTICLE 19


In response to the International Search Report mailed March 3, 2004, please amend the above-identified International PCT application by replacing pages 11-14 of the application with the attached substitute pages. In the substitute pages 11-14, original claims 8, 28, and 29 have been amended, claim 27 has been deleted, and amended claims 28 and 29 have been renumbered as claims 27 and 28.

Respectfully submitted,

JOHNSON CONTROLS TECHNOLOGY COMPANY

By: Price, Heneveld, Cooper, DeWitt & Litton, LLP

June 14, 2004
Date


H. W. Reick
Registration No. 25 438
695 Kenmoor S.E.
P.O. Box 2567
Grand Rapids, MI 49501
(616) 949-9610

HWR:dal

7. The assembly as defined in claim 6 wherein said cover includes a recess which surrounds the lens and allows the cover to move with respect to the frame and lens.
8. An illuminated vanity mirror assembly comprising:
a mirror frame adapted to receive a mirror therein, said mirror frame including a lamp for illuminating said mirror, said frame including a pair of spaced-apart cover receiving sockets near an edge of said frame, wherein one of said sockets comprises a cylindrical socket for captively holding a pivot axle therein and the other socket is an open socket for allowing the snap-in assembly of a cover to said frame, said frame further including at least one detent spring receiving socket;
a cover including integrally formed first and second pivot axles for extending within said cylindrical and open sockets, said cover including a cam aligned with said detent spring for providing snap open and closed control of said cover; and
a lens coupled to said frame for holding at least one of said cover pivot axles within said frame.
9. The assembly as defined in claim 8 wherein said mirror frame is molded of a polymeric material and includes an insert-molded electrical circuit including contacts adapted to engage conductors of a visor core when said vanity mirror assembly is mounted to a visor core.
10. The assembly as defined in claim 9 wherein said electrical circuit further defines a lamp socket for receiving a lamp.
11. The assembly as defined in claim 10 wherein said electrical circuit further includes a switch including a deflectable switch contact.
12. The assembly as defined in claim 11 wherein one pivot axle of said cover further includes a switch cam which selectively engages said deflectable contact for actuating said switch when said cover is in an open position to provide operating power to a lamp positioned in said lamp socket.

13. An electrical assembly for a visor comprising:

a housing adapted to receive an electrical component therein; wherein the improvement comprises:

said housing is molded of a polymeric material and includes an insert-molded electrical circuit which is coupled to an electrical component within said housing and wherein said electrical circuit includes contacts adapted to engage contacts of a visor core when said housing is assembled to a visor core for coupling to an electrical supply available in said core to said electrical component.

14. The assembly as defined in claim 13 wherein said housing is an illuminated vanity mirror frame and said electrical component is a lamp.

15. The assembly as defined in claim 14 and further including a cover pivotally mounted to said mirror frame and wherein circuit further includes a switch including a deflectable element engaged by said cover for actuating said switch when said cover is in an open position to provide operating power to said lamp.

16. A visor and vanity mirror assembly comprising:

a visor body having at least one electrical conductor for coupling to a vehicle electrical system; and

a mirror frame adapted to receive a mirror therein, wherein said mirror frame is molded of a polymeric material and includes an insert-molded electrical circuit which is coupled to an electrical component within said mirror frame and wherein said electrical circuit includes at least one contact adapted to engage said conductor of said visor body when said frame is assembled to said visor body for coupling an electrical supply available in said body to said electrical component.

17. The assembly as defined in claim 16 wherein said visor body includes at least one conductor holding ledge for positioning an insulated electrical conductor having a stripped end exposing the conductor in a position to be engaged by said contact of said electrical circuit.

18. The assembly as defined in claim 17 wherein said visor body includes a first ledge including a hook for holding said conductor to said visor body and a second ledge including a notch for receiving and holding a stripped end of said conductor in a fixed position.

19. The assembly as defined in claim 18 wherein said contact of said electrical circuit includes a pair of spaced-apart spring loaded walls which extend over said second ledge of said visor body and compressibly engage said stripped end of said conductor held in said notch to make an electrical contact with said conductor when said frame is mounted to said visor body.

20. The assembly as defined in claim 19 wherein one of said walls of said contact includes a slot for surrounding said conductor when said frame is mounted to said visor body.

21. The assembly as defined in claim 20 wherein said electrical circuit is made of stainless steel.

22. The assembly as defined in claim 21 wherein said frame includes locking tabs and said visor body includes slots for securing said frame to said visor body.

23. The assembly as defined in claim 22 wherein said electrical component is a lamp for illuminating said mirror.

24. The assembly as defined in claim 23 and further including a cover pivotally mounted to said mirror frame and wherein circuit further includes a switch including a movable contact engaged by said cover for actuating said switch when said cover is in an open position to provide operating power to said lamp.

25. The assembly as defined in claim 24 wherein said mirror frame includes an enclosed cylindrical socket and an open semi cylindrical socket longitudinally spaced from said closed socket, said frame further including at least one detent spring receiving

socket; and wherein said cover includes a first pivot axle extending within said closed cylindrical socket and a second pivot axle snap-fitted within said semi cylindrical socket, said cover including a cam associated with said cover; and

a detent spring positioned within said detent spring receiving socket of said mirror frame and extending between said mirror frame and engaging an associated cam of said cover for providing snap open and close control of said cover.

26. The assembly as defined in claim 25 and further including a lens coupled to said frame for holding said second pivot axle within said semi cylindrical socket.

27. A visor and vanity mirror assembly comprising:

a visor body;

a mirror frame adapted to receive a mirror therein and cover receiving sockets near an edge of said frame for allowing the snap-in assembly of a cover to said frame;

a cover having first and second pivot axles for extending within said sockets; and

a lens coupled to said frame for holding at least one of said cover pivot axles within said frame, wherein said sockets of said mirror frame include an enclosed cylindrical socket and an open semi cylindrical socket longitudinally spaced from said closed socket, and wherein said cover includes a first pivot axle extending within said closed cylindrical socket and a second pivot axle snap-fitted within said semi cylindrical socket; and said lens holds said second pivot axle in said semi cylindrical socket.

28. The assembly as defined in claim 27 wherein said mirror frame includes a lamp for illuminating said mirror and wherein said mirror frame is molded of a polymeric material and includes an insert-molded electrical circuit including contacts adapted to engage contacts of said visor body when said vanity mirror assembly is mounted to said visor body.